

NEW PRODUCTS FEATURED IN THE NE 1 1 CATALOGUE:

PUSH-IN CONNECTOR FOR EMT - PAGE 15



- * **QUICKLY JOIN EMT CONDUIT TO A BOX OR ENCLOSURE**
- * **ZINC DIE CAST MATERIAL**
- * **TRI-COMBO SCREW**

COLOUR CODE EMT FITTINGS - PAGE 19 - 21



- * **COLORED FITTINGS MATCH COLORED EMT RACEWAYS FOR CLEAN LOOKING INSTALLATIONS**
- * **STEEL FITTING WITH TRI-COMBO SCREW**
- * **COLOURS AVAILABLE: RED, WHITE, BLUE, GREEN, YELLOW, BLACK, ORANGE**



RED FIRE ALARM BOXES - PAGE 21

- * **NEW RED STEEL FIRE ALARM BOXES TO MEET VISUAL IDENTIFICATION**



BONDING LOCKNUTS - PAGE 24

- * **USED IN HARSH VIBRATION ENVIRONMENTS TO FASTEN THREADED CONDUIT TO AN UNTHREADED OPENING IN A BOX OR ENCLOSURE**



SEALING LOCKNUTS - STEEL- PAGE 24

- * **Steel locknut with PVC seal used to provide liquid tight seal when fastening threaded conduit to unthreaded opening in a box or enclosure**



SPLIT THREADED RIGID CONDUIT COUPLING - PAGE 29

- * **1/2" thru 6" Split Threaded Rigid Conduit Couplings used to join two lengths of threaded rigid and IMC conduit**

NEW PRODUCTS FEATURED IN THE NE 1 1 CATALOGUE:

RAINTIGHT 3-PIECE COUPLING - PAGE 29



- * Used to join two lengths of threaded rigid or IMC conduit. cULus Listed.
- * Self-Aligning
- * **MALLEABLE IRON**

COMBINATION LIQUID TIGHT TO RRAINTIGHT EMT CONNECTOR - PAGE 43



- * Used to join either metallic or non-metallic (Type B") liquid tight conduit to EMT

MULTI-ANGLE NONMETALLIC LIQUID TIGHT CONNECTOR (0-90°) - PAGE 46



- * Eliminate inventory - the swivel design can be substituted for a Straight or 90° connector. Ships assembled with steel lock-nut and rubber O-ring.

COMBINATION EMT TO AC/MC COUPLING PAGE 51



- * Used to securely join EMT to two armored or metal clad cables. A labour savings, compared to the traditional junction box installation.

STAINLESS STEEL JACK CHAIN - #10 - PAGE 54



- * For use in corrosive environments
- * Available in 100' boxes

COLD WEATHER TAPE - PAGE 55



- * **Premium quality COLD and Weather Resistant Electrical Tape**
- * **WORKING TEMPERATURE RANGE OF -18°C TO 80°C. POLAR250 WITH ITS MEMORY (ELASTICITY), 8.5MIL THICKNESS AND ADHESION CHARACTERISTICS PROVIDES MOISTURE-TIGHT ELECTRICAL PROTECTION.**
- * **EACH ROLL IS PACKAGED IN A PROTECTIVE PLASTIC CASE.**

NEW PRODUCTS FEATURED IN THE NE 11 CATALOGUE:



ELECTRICAL BOX EXTENDER / INSULATOR - PAGE 57

- * Easier to install design. Eliminates the need to align device screws with extender holes.
- * Continuous, smooth, nonmetallic side walls insulate device such as GFCI from metallic box.
- * Extender does not interfere with wiring. No trimming required.



LOW VOLTAGE DEVICE HOLDERS - NEW WORK

- * Available as a single gang or double gang low voltage device holder
- * To be used for new work on 2x4 or steel stud with 1/2" or 3/4" EMT.



STEEL DATA PLATE MOUNTING BRACKET - PAGE 57

- * Eliminates need for outlet box. Provides mounting base for securing com-



TAYMAC WEATHERPROOF PRODUCTS

TOPAZ WEATHERPROOF LIGHTING - PAGE 78-85



- * High Quality weatherproof covers, outlet boxes and accessories
- * In-Use Covers—Plastic and Metal design in a variety of depths
- * **CAST BOXES AND COVERS AVAILABLE IN GREY, WHITE AND BRONZE**

